

SECTION 08 11 16

INTERIOR ALUMINUM DOORS AND FRAMES / SWING DOORS

CSI - CONSTRUCTION SPECIFICATION INSTITUTE OUTLINE

The Sliding Door Company's door and frame system includes glazed swing doors, sidelights, transoms, and fixed panels to create a sophisticated system for interior doorways and office fronts. Ideal for green construction projects, the laminated glass and aluminum are recyclable. The systems are easily installed, designed to allow for natural light and even offer solutions to save energy and money. Visit any of our showrooms in North America to experience the functionality and the range of design possibilities. Documents related to our interior glass and aluminum doors and frames are available at <https://www.slidingdoorco.com/for-trade/>.

Drawing Coordination:

Client provided layouts should include locations of doors and glazed lights, directions of operation, and sizes of openings in addition to surrounding structures. If formal shop drawings are required, they will be indicated on the estimate and order forms for each specific project.

The Sliding Door Company (USA and Canada)

Toll Free: 888-433-1333

Email: salessupport@slidingdoorco.com

Web: <https://www.slidingdoorco.com/for-trade/>

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes interior aluminum-framed glass doors [, glazed panels,] and frames.
- B. Related Requirements:
 - 1. Section 08 71 00 – Door hardware, optional locks, latches, keys.
- C. References:
 - 1. American Society for Testing and Materials (ASTM).
 - a. ASTM B221, Aluminum 6063-T6 Standard Structural Profiles.
 - b. ASTM C1048, Heat-Treated Flat Glass – Kind HS, Kind FT Coated and Uncoated Glass.
 - c. ASTM C1172, Laminated Architectural Flat Glass.
 - d. ASTM C1036, Standard Specification for Flat Glass.
 - 2. American Architectural Manufacturers Association (AAMA).
 - a. AAMA 611, Anodized Architectural Aluminum.
 - 3. American National Standards Institute (ANSI).
 - a. ANSI Z97.1-2015 (R2020).
 - 4. International Building Code 2024 (IBC 2024).
 - 5. U.S. Consumer Product Safety Commission (CPSC).
 - a. CPSC 16 CFR 1201, Category II, Safety Standard for Architectural Glazing Materials.
 - 6. California Referenced Standards Code (CRSC).
 - a. CRSC 12-10-202, Design.

1.2 ADMINISTRATIVE REQUIREMENTS

- A. Field-verify dimensions and clearances for openings scheduled to receive work of this section.
 - 1. Our door solutions can accommodate ADA requirements.
 - 2. Alternatively: If openings are not yet built, client may “Build to approved shop drawing, (hold to dimensions)”.
- B. Scheduling:
 - 1. Ordering and Delivery: Order products with sufficient lead time to avoid delays in project schedule.
 - 2. Installation: To extent practical, install work after surrounding finish work is complete. (Last trade in)

1.3 ACTION SUBMITTALS

- A. Product Data: Include fabrication details, frame finishes, glass types, installation details and operating instructions. (See Section 3.2)
- B. Shop Drawings (for a fee):
 - 1. Include plans, elevations, details, hardware, operational clearances and accessories. **[Include keying schedule for locksets.]** if applicable.
 - 2. Delegated Design Submittals: If a client’s project requires dimensions and conditions that fall outside of what our product is designed to do the client will be responsible to provide engineering calculations for their specific project, demonstrating compliance with applicable regulations.
- C. Samples for Verification:
 - 1. Extrusions: Frame finish samples include all available options.
 - 2. Glass: Approximately 3 inches square.
- D. Warranty: Submit sample of manufacturer’s standard warranty.

1.4 CLOSEOUT SUBMITTALS

- A. Operation and maintenance data.
- B. Executed warranty.
- C. A copy of the signed / approved drawings.

1.5 QUALITY ASSURANCE

- A. Installer: **[Approved by manufacturer or client provided installation company.]**
 - 1. A general contractor is not required to install our interior glass door solutions.
 - 2. Client has ownership for installation if a non-TSDC installer is selected.
- B. Non-TSDC Installers: Client provided installers/Licensed in project jurisdiction.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Delivery: Deliver products after space is enclosed, secured, and wet work is complete.
- B. Acceptance: Inspect packaging and report noticeable damage to manufacturer within 48 hours of receiving.
- C. Storage: Store in original packaging, up to ten degrees from vertical, on level floor surface.
- D. Handling: Handle in accordance with manufacturer's installation instructions and to prevent damage.

1.7 WARRANTY

- A. See separate warranty document.

PART 2 - PRODUCTS

2.1 MANUFACTURER

- A. Manufacturer: **The Sliding Door Company**
20235 Bahama St., Chatsworth, CA 91311
Toll Free: 888-433-1333
Email: salesupport@slidingdoorco.com
Web: www.slidingdoorco.com
- B. The Sliding Door Company provides factory-to-field support and turnkey solutions.
- C. Substitutions:
 - 1. No substitutions.

2.2 COMPONENTS

- A. Framing, General:
 - 1. Material: Aluminum extrusions, 6063 alloy.
 - 2. Finish:
 - a. **[Clear Anodized Aluminum: AAMA 611, Class II.]**
 - b. **[Powder Coating: [White][Black][Charcoal][Champagne].]**
- B. Heads, Jambs, Beams, and Columns:
 - 1. Profiles:
 - a. Head and Jamb: 3.5 – 7.5 inches deep.
 - b. Head and Jamb Trim: 2 inch wide.
 - c. Attachable Door Stop: **[1.5 inch wide by 0.5 inch]**, 0.05 inch minimum thickness.
 - d. Beams: **[2 by 4 inches][4 by 4 inches]**, 0.102 inch minimum thickness.
 - e. Columns: **[2 by 4 inches][4 by 4 inches]**, 0.102 inch minimum thickness.
- C. Stiles, Rails and Mullions:
 - 1. Stile and Rail Widths:
 - a. **[1.5 inch wide, 0.051 inch minimum thickness.]**
 - b. **[3 inch wide, 0.051 inch minimum thickness.]**

PLEASE CONTACT US SHOULD YOU REQUIRE EDITABLE COPIES OF OUR SPECIFICATIONS AND DATA SHEETS
salesupport@slidingdoorco.com

2. Kickplate: 10-inch door bottom rail is optional, for inclusion on doors required to meet ADA accessibility guidelines. **[Door Bottom Rail: 10 wide.]**

3. Mullions:

a. Built-In Mullions: **[1.5][3]** inch wide.

1) For use with Laminated Glass, we highly recommend a maximum of one built-in mullion per panel (when panel exceeds maximum size in height or width).

2) For use with Tempered Glass, additional built-in mullions may be used.

b. Surface Applied Mullions: **[1.5][3]** inch wide.

1) Used for design (both Laminated and Tempered).

2) Not recommended for applications with Mirror.

D. Glass: Category II Safety Glazing per CPSC 16 CFR 1201.

1. Monolithic Clear Tempered Glass: 5mm, or 10mm from our thick glass series, ASTM C1048, Kind FT.

a. **[Back Painting: [None][Milky][Deluxe White][Black].]**

b. Glazing Patterns:

1) **Commercial Frosted Film: Poly(vinyl) chloride with bonded plasticizer.**

2) **“Combo” (Clear and Commercial Frosted Film):**

a) Commercial Frosted Film and Clear: Apply Commercial Frosted Film to a partial client-selected section [to specified height above finished floor.][as shown on Drawings.]<Other Description]

3) **Waterfall: Reeded glass.**

4) **Smoked (Clear, Frosted, Milky)**

2. Laminated Glass: ASTM C1172, 7mm or 11mm from our thick glass series, with **[White][Opaque][Clear]** interlayer.

3. Mirror: **[Standard][Smoked]** annealed mirrored glass, ASTM C1036, with safety film backing.

2.3 HARDWARE

A. Handles:

1. Standard Handle (Black, White, Brushed Silver - Aluminum) **[Single][Double]**.

2. Round Designer Handle (Black, Gold, Brushed Silver - Stainless Steel) **[Single][Double], [9” ht][12” ht][14”ht] x [5/8” Dia]**.

3. Square Designer Handle (Black, Gold, Brushed Silver - Aluminum) **[Single][Double], [8” ht][10” ht][12” ht]**.

4. Extended Square Designer Handle (Black, Gold, Brushed Silver - Stainless Steel) **[Single][Double], [11” ht][23-5/8” ht]**.

5. Ladder Handle (Black, Gold, Brushed Silver - Stainless Steel) **[Single][Double], [24” ht][36” ht]**

B. Locks and Latches:

1. Lever Set: Passage set (No lock, Black, Brushed Silver - Stainless Steel).

2. Residential Lever (Black, Brushed Silver - Stainless Steel)

3. Lever Locking Set ADA (Black, Brushed Silver - Stainless Steel): [Lever with thumb turn (one side) [Lever with thumb turn and key lock].

a. Keying: Provide [two]<Other number> keys per lockset, labeled to indicate door. [Key lock sets uniquely [and provide two master keys].]

4. Keyless Smart Lock (Black, Silver - Stainless Steel, Aluminum/Plastic)

a. Keying: Provide [three]<Other number> keys per lockset, labeled to indicate door. [Key locksets uniquely [and provide three master keys].]

5. Latch Mechanism with 1” Cylinder and Thumbturn for Swing Doors (Black, Brushed Silver - Stainless Steel): [Lever with thumb turn and key lock].

a. Keying: Provide [three]<Other number> keys per lockset, labeled to indicate door. [Key

- locksets uniquely [and provide three master keys].]
6. Latch Mechanism with 1" Cylinder and Thumbturn for Swing Doors - U-Lever (Black, Brushed Silver - Stainless Steel): [Lever with thumb turn and key lock].
 - a. Keying: Provide [three]<Other number> keys per lockset, labeled to indicate door. [Key locksets uniquely [and provide three master keys].]
 7. Latch Mechanism with 1" Mortise and Electric Strike Plate (Black, Brushed Silver - Stainless Steel): [Lever with key lock (one side)][Lever (other side)]
 - a. Keying: Provide [three]<Other number> keys per lockset, labeled to indicate door. [Key locksets uniquely [and provide three master keys].]
 - b. Client to provide access control security system to be connected with wires to electrical strike plate to control functionality. (12 or 24 volt DC)
 8. Flush Slide Bolt (Black, Brushed Silver - Aluminum)
 9. Ball Catch (Brushed Silver - Stainless Steel)

C. Pivots: Top pivot hinge and bottom pivot.

2.4 FABRICATION AND ASSEMBLY

A. Door Design:

1. [Solo: Single light.]
2. [Trio: Divided horizontally into three lights.]
3. [Quattro: Divided horizontally into four lights.]
4. [Pentagon: Divided horizontally into five lights.]
5. [Duo-T: Large center light with pairs of lights above and below.]
6. [Continental: Grid, four lights high by two lights wide.]
7. Custom.

B. Factory Assembly: Unitized system, includes assembled glass and frame to the custom size specified [, except provide field splicing at locations indicated in shop drawings to accommodate handling and access limitations] for beam/columns (if applicable).

2.5 ACCESSORIES

- A. Silicone Adhesive (provided by client): Clear, construction grade silicone adhesive.
- B. Fasteners: As indicated in Shop Drawings.

PART 3 - EXECUTION

3.1 EXAMINATION

A. Verify that openings and substrates are acceptable for installation of work of this section. This is part of "site readiness".

3.2 INSTALLATION

A. Install systems according to shop drawings and manufacturer's product data and installation instructions.

PLEASE CONTACT US SHOULD YOU REQUIRE EDITABLE COPIES OF OUR SPECIFICATIONS AND DATA SHEETS
salesupport@slidingdoorco.com

B. Reference QR code for installation instructions list.



3.3 ADJUSTING, CLEANING AND PROTECTION

- A. Adjust swing doors for smooth operation.
- B. Comply with manufacturer's written recommendations for cleaning and maintenance.
- C. Clean aluminum and glass surfaces immediately after installing doors and frames.
- D. Protect surfaces from impact and from contact with contaminating substances resulting from other construction operations. Typically, this product is last trade in.
- E. Clean immediately before Substantial Completion.

3.4 CLOSEOUT REQUIREMENTS

- A. **[Deliver keys as specified in Section 08 71 00 - Door Hardware.][Deliver keys directly to Owner.]** (Only applicable if keys/locks are included in the project.)
- B. Deliver executed Warranty.
- C. Copy of operations manual.
- D. Copy of approved drawings.

NOTE: Client has full ownership for site conditions and readiness prior to The Sliding Door Company product being installed.

END OF SECTION

Copyright 2026 by The Sliding Door Company. Qualified design and construction professionals may copy for preparation of construction specifications. Issued: January 2026.

PLEASE CONTACT US SHOULD YOU REQUIRE EDITABLE COPIES OF OUR SPECIFICATIONS AND DATA SHEETS
salessupport@slidingdoorco.com